

**Hardware:**

Tape, included or installed on ladder

**Tools Needed:**

Philips screw driver  
Torx T30  
10 mm Socket and driver  
10 mm wrench  
Marker or painters tape  
Rubbing alcohol



## Installation Instructions Rear Access Ladder

**Installation Instructions:**

Open rear hatch to remove rubber weather seal (pull slightly to one side and down and the seal will release), remove trim around the latch, remove screw & cover for interior latch handle.

Use Torx T30 to remove Torx bolts

The interior plastic piece is now ready to be removed. It is held onto the car by plastic body pins. To remove carefully pull apart. Start with a corner. If some of the pins remain in the car body remove these pins and reposition to the interior molding. Set aside.

Locate the (3) 10 mm bolts that secure your exterior hatch latch and remove.

Disconnect electrical plug and remove latch. Set aside.

Clip ladder onto top of hatch and mark with 2 pieces of tape (one on each side of the ladder. Align ladder to vehicle.

Remove ladder,

Clean between tape marks with alcohol or wax/grease remover. Remove adhesive backing from double sided tape

Place Ladder on vehicle at marked position making sure the top of the ladder clips to the vehicle and the ladder aligns with the marks/tape.

Pull Ladder down to align ladder with latch holes.

Reconnect latch assembly, tighten bolts.

Replace interior pieces, Torx bolts and rubber weather seal.

Enjoy your new ladder!

**Applications:**

LR3 Discovery 3

LR4 Discovery 4

Model Years: 2005-2015



## Hardware:

Tape, included or installed on ladder

## Tools Needed:

Philips screw driver  
Torx T30  
10 mm Socket and driver  
10 mm wrench  
Marker or painters tape  
Rubbing alcohol



# Installation Instructions Rear Access Ladder

## Installation Instructions:

Open rear hatch to remove rubber weather seal (pull slightly to one side and down and the seal will release), remove trim around the latch, remove screw & cover for interior latch handle.

Use Torx T30 to remove Torx bolts

The interior plastic piece is now ready to be removed. It is held onto the car by plastic body pins. To remove carefully pull apart. Start with a corner. If some of the pins remain in the car body remove these pins and reposition to the interior molding. Set aside.

Locate the (3) 10 mm bolts that secure your exterior hatch latch and remove.

Disconnect electrical plug and remove latch. Set aside.

Clip ladder onto top of hatch and mark with 2 pieces of tape (one on each side of the ladder. Align ladder to vehicle.

Remove ladder,

Clean between tape marks with alcohol or wax/grease remover. Remove adhesive backing from double sided tape

Place Ladder on vehicle at marked position making sure the top of the ladder clips to the vehicle and the ladder aligns with the marks/tape.

Pull Ladder down to align ladder with latch holes.

Reconnect latch assembly, tighten bolts.

Replace interior pieces, Torx bolts and rubber weather seal.

Enjoy your new ladder!

Applications:

LR3 Discovery 3

LR4 Discovery 4

Model Years: 2005-2015

